




Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM3-IE3 250M4**

Rated power **55 kW S1 Duty**

Speed **1485 rpm**

Voltage **400V / 690V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **97.6 A / 56.6 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M63 x 1.5**

Construction **Cast Iron**

Weight **456 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data 100% 75% 50% 25%

Efficiency **94.6% 94.6% 92.8%**

Power factor **0.86**

Sound pressure level (1m) **79 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **353.7 Nm**

Starting / Full load torque **2.6**

Pull up / Full load torque

Pull out / Full load torque **3**

Starting / Full load current (DOL) **8.5**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6314**

Bearing NDE **6313**

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk