




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM4-IE4 250M4**
 Rated power **55 kW S1 Duty**
 Speed **1485 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **96.5 A / 55.9 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M63 x 1.5**
 Construction **Cast Iron**
 Weight **492 Kg**
 Type number
 Warranty

Efficiency class **IE4**
 Load data 100% 75% 50% 25%
 Efficiency **95.7%**
 Power factor **0.86**
 Sound pressure level (1m) dB(A)
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **353.7 Nm**
 Starting / Full load torque **2.99**
 Pull up / Full load torque
 Pull out / Full load torque **3.12**

Starting / Full load current (DOL) **9**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6314**
 Bearing NDE **6313**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk