




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAS-R-IE2 80 G2
Rated power	1.1 kW S1 Duty
Speed	2850 rpm
Voltage	220V
Frequency	50 Hz
Connection	Single Phase
Full load current	6.13 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20x1.5
Construction	Aluminium
Weight	11.2 Kg
Type number	
Warranty	
Run Capacitor	30uf/450V

Efficiency class	IE2
Load data	100% 75% 50% 25%
Efficiency	79.6%
Power factor	0.98
Sound pressure level (1m)	75 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	3.69 Nm
Starting / Full load torque	0.4
Pull up / Full load torque	
Pull out / Full load torque	1.9

Starting / Full load current (DOL)	
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6204
Bearing NDE	6204

Protection Device **Thermal Reset Switch**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk