




Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM3-IE3 225M4**

Rated power **45 kW S1 Duty**

Speed **1480 rpm**

Voltage **400V / 690V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **80.2 A / 46.5 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M40 x 1.5**

Construction **Cast Iron**

Weight **343 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data 100% 75% 50% 25%

Efficiency **94.2% 94.3% 92.7%**

Power factor **0.86**

Sound pressure level (1m) **78 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **290.4 Nm**

Starting / Full load torque **2.6**

Pull up / Full load torque

Pull out / Full load torque **3.2**

Starting / Full load current (DOL) **8.5**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6313**

Bearing NDE **6312**

AmTecs Ltd		
Charnham Park, Hungerford		
Berkshire, RG17 0YT		
Tel: +44 (0) 1488 686970		sales@amtecs.co.uk
Fax: +44 (0) 1488 686968		www.amtecs.co.uk