
AMA-IE2 90S8 (B3)

AMTECS



A	B	C	D	E	F	G	H	K	AB	BB	AC	AD	HD	L
140	100	56	24	50	8	20		10	177	125	175	145	235	308

AMTECS LTD

TITLE
AMA (B3)

SIZE | DWG NO | REV

SCALE 1 / 2 | AMA 112M-B3 | SHEET 1 OF 1

This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

Specification	**IEC 60034-1**
Manufacturer	**AmTecs**
Motor type	**AMA-IE2 90S8**
Rated power	**0.37** kW **S1** Duty
Speed	**710** rpm
Voltage	**400V / 690V**
Frequency	**50** Hz
Connection	**Delta / Star**
Full load current	**1.59 A / 0.92 A**
No-load current	
Enclosure	**IP55**
Insulation class	**F (temp. rise B)**
Max. ambient temp	**40** °C
Max. altitude	**1000** mtr above sea level
Comment	
Cable entry	**M20 x 1.5**
Construction	**Aluminium**
Weight	**18.5** Kg
Type number	
Warranty	

Efficiency class			**IE2**		
Load data	100%	75%	50%	25%	
Efficiency	**56.1%**				
Power factor			**0.6**		
Sound pressure level (1m)			**54**	dB(A)	
Resistance R20 (open)					
Resistance R20 (Delta)					
Full load torque			**5**	Nm	
Starting / Full load torque			**1.9**		
Pull up / Full load torque					
Pull out / Full load torque			**2**		
Starting / Full load current (DOL)			**4**		
Starting / Full load current (Y/D)					
Rotor Inertia					
Bearing DE			**6205**		
Bearing NDE			**6205**		

AmTecs Ltd
Charnham Park, Hungerford
Berkshire, RG17 0YT
Tel: +44 (0) 1488 686970
Fax: +44 (0) 1488 686968
sales@amtecs.co.uk
www.amtecs.co.uk

We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.