




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMAH-IE3 132M2**
 Rated power **9.2 kW S1 Duty**
 Speed **2930 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **16.7 A / 9.64 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M25 x 1.5**
 Construction **Aluminium**
 Weight **55 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data 100% 75% 50% 25%
 Efficiency **90.6%**
 Power factor **0.88**
 Sound pressure level (1m) **70 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **30 Nm**
 Starting / Full load torque **2.2**
 Pull up / Full load torque
 Pull out / Full load torque **3.2**

Starting / Full load current (DOL) **8.8**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6308**
 Bearing NDE **6308**

Protection Device **PTC 150**

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk