




Specification
Manufacturer AmTecs
Motor type AM3-IE3 315M4
Rated power 132 kW S1 Duty
Speed 1480 rpm
Voltage 400V / 690V
Frequency 50 Hz
Connection Delta / Star
Full load current 226.5 A / 131.3 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M63 x 1.5
Construction Cast Iron
Weight 994 Kg
Type number
Warranty

Efficiency class IE3
Load data 100% 75% 50% 25%
Efficiency 95.6% 95.1% 93.3%
Power factor 0.88
Sound pressure level (1m) 88 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 851.8 Nm
Starting / Full load torque 2.5
Pull up / Full load torque
Pull out / Full load torque 2.7

Starting / Full load current (DOL) 8.2
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE NU319
Bearing NDE 6319

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
sales@amtecs.co.uk www.amtecs.co.uk	