
# AMA3-IE3 100LX8 (B14S)

AMTECS






Remarks:

1. Glands: 1 off M20 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M20 x 1.5
2. Eye bolt M8

| | | | |
|---|---|---|---|
| DRAWN | JamesSouter | 29/01/2024 | AMTECS |
| CHECKED | Oliver Young | 31/01/2024 | TITLE: AMA3-IE3 100L (B14S) |
| QA | | | |
| MFG | | | |
| APPROVED | | | |
| SIZE: A3 | | DWG NO: AMA3-IE3 100L (B14S) | REV |
| SCALE: 1 / 4 | | | SHEET 1 OF 1 |

| | | | |
|---|---|---|---|
| Specification | **IEC 60034-1** | Efficiency class | **IE3** |
| Manufacturer | **AmTecs** | Load data | 100% 75% 50% 25% |
| Motor type | **AMA3-IE3 100LX8** | Efficiency | **77.7%** |
| Rated power | **1.1** kW **S1** Duty | Power factor | **0.69** |
| Speed | **710** rpm | Sound pressure level (1m) | **49** dB(A) |
| Voltage | **220V / 400V** | Resistance R20 (open) | |
| Frequency | **50** Hz | Resistance R20 (Delta) | |
| Connection | **Delta / Star** | | |
| Full load current | **5.15 A / 2.96 A** | Full load torque | **14.8** Nm |
| No-load current | | Starting / Full load torque | **1.8** |
| Enclosure | **IP55** | Pull up / Full load torque | |
| Insulation class | **F (temp. rise B)** | Pull out / Full load torque | **2** |
| Max. ambient temp | **40** °C | | |
| Max. altitude | **1000** mtr above sea level | | |
| Comment | | | |
| Cable entry | **M20 x 1.5** | Starting / Full load current (DOL) | **6.2** |
| Construction | **Aluminium** | Starting / Full load current (Y/D) | |
| Weight | Kg | Rotor Inertia | |
| Type number | | Bearing DE | **6206** |
| Warranty | | Bearing NDE | **6206** |


**AmTecs Ltd**
Charnham Park, Hungerford
Berkshire, RG17 0YT
Tel: +44 (0) 1488 686970
Fax: +44 (0) 1488 686968
sales@amtecs.co.uk
www.amtecs.co.uk



*We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.*