




Specification **IEC 60034-1**  
 Manufacturer **AmTecs**  
 Motor type **AM4-IE4 200LX2**  
 Rated power **37 kW S1 Duty**  
 Speed **2970 rpm**  
 Voltage **400V / 690V**  
 Frequency **50 Hz**  
 Connection **Delta / Star**  
 Full load current **63.3 A / 36.7 A**  
 No-load current  
 Enclosure **IP55**  
 Insulation class **F (temp. rise B)**  
 Max. ambient temp **40 °C**  
 Max. altitude **1000 mtr above sea level**  
 Comment  
 Cable entry **M40 x 1.5**  
 Construction **Cast Iron**  
 Weight **262 Kg**  
 Type number  
 Warranty

Efficiency class **IE4**  
 Load data 100% 75% 50% 25%  
 Efficiency **94.8%**  
 Power factor **0.89**  
 Sound pressure level (1m) dB(A)  
 Resistance R20 (open)  
 Resistance R20 (Delta)

Full load torque **119 Nm**  
 Starting / Full load torque **2.7**  
 Pull up / Full load torque  
 Pull out / Full load torque **3**

Starting / Full load current (DOL) **9**  
 Starting / Full load current (Y/D)  
 Rotor Inertia  
 Bearing DE **6212**  
 Bearing NDE **6212**

|                           |                    |
|---------------------------|--------------------|
| <b>AmTecs Ltd</b>         |                    |
| Charnham Park, Hungerford |                    |
| Berkshire, RG17 0YT       |                    |
| Tel: +44 (0) 1488 686970  | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968  | www.amtecs.co.uk   |